

Oxford® Elite Smooth Texture 6cm



Product	Pieces / Sq. Ft. Per Layer / Pallet	Layers / Sq. Ft. Per Pallet	Weight Per Pallet / Sq. Ft.
Oxford Elite Square <i>sold by the layer</i>	13.44 sq. ft. per layer 64 pcs./layer	8 layers/pallet = 1 sq. ft.	2,944 lbs./pallet 27.4 lbs./sq. ft.
Oxford Elite Rectangle <i>sold by the layer</i>	12.6 sq. ft. per layer 40 pcs./layer	8 layers/pallet = 1 sq. ft.	2,773 lbs./pallet 27.5 lbs./sq. ft.

APPEARANCE

Edge Detail - Pillow Top/Rounded
Surface Texture - Smooth
Joint Spacing - 2.2 mm

TECHNOLOGIES

Face Texture - Elite Face-Mix Technology

TECHNICAL INFORMATION

Conforms to ASTM C936
Eligible for LEED v4.1 credits


APPLICATIONS

Pedestrian
Residential Vehicular


INSTALLATION METHODS

Hand


PATTERNS



MUSTER D




MUSTER K




BUCKHORN



CRIMSON



COAL



MESQUITE



MIDNIGHT SKY



SQUARE
(H) 2 5/8" x (D) 5 1/2" x (L) 5 1/2"



RECTANGLE
(H) 2 5/8" x (D) 5 1/2" x (L) 8 1/4"

Reading Rock recommends using a roller compactor on PaverLock Elite pavers.



Available At:



LEEBP.COM