



# MAXBRIC™

Maximum Value. Maximum Performance.


**4" UTILITY SIZE - CORED**  
UNIT WT: 10.0 LBS.




**4" UTILITY SIZE - SOLID**  
UNIT WT: 11.4 LBS.




**4" REGULAR - CORE PATTERN 1**  
UNIT WT: 11.8 LBS.




**4" REGULAR - CORE PATTERN 2**  
UNIT WT: 11.8 LBS.




**4" REGULAR - CORE PATTERN 3**  
UNIT WT: 11.2 LBS.




**4" REGULAR - SOLID**  
UNIT WT: 13.0 LBS.




**8" CORNER / SASH**  
UNIT WT: 16.25 LBS.




**10" CORNER / SASH**  
UNIT WT: 22.8 LBS.




**12" CORNER / SASH**  
UNIT WT: 25.5 LBS.




**8" HALF UNIT/SASH**  
UNIT WT: 10.4 LBS.




**12" HALF UNIT/SASH**  
UNIT WT: 13.0 LBS.




**8" RESTRICTED BOTTOM BOND BEAM**  
UNIT WT: 16.25 LBS.




**12" RESTRICTED BOTTOM BOND BEAM**  
UNIT WT: 22.5 LBS.




**8" PILASTER**  
UNIT WT: 16.25 LBS.




**10" PILASTER**  
UNIT WT: 22.8 LBS.



**12" PILASTER**  
UNIT WT: 25.5 LBS.



**8" STRETCHER**  
UNIT WT: 16.25 LBS.



**12" STRETCHER**  
UNIT WT: 25.5 LBS.

