




ANTIKA

DESCRIPTION: Paver **TEXTURE:** Smooth and Aged

PALLET OVERVIEW*



The Antika paver is perfect as a filler in a circle, around a fan design or on a winding pathway. Antika can also be used as a mosaic frame around any design.


NOTES

See page 44 to 47 for more technical information. When used in a permeable pavement application, see page 89 to 95 for more technical information.

JOINT WIDTH: VARIABLE
% OF SURFACE OPENING: VARIABLE
INFILTRATION RATE: 993 IN./HR
 (25 227 MM/HR)

*Pallet layout may vary.

01 | Random pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Specifications per pallet	Imperial	Metric
Cubing	87 ft²	8.10 m ²
Approx. Weight	2 183 lbs	990 kg
Number of rows	9	
Coverage per row	9.67 ft ²	0.90 m ²

	Unit dimensions	in	mm
A		Height: 2 3/8	60
		Width: Variable	
		Length: Variable	
B		Height: 2 3/8	60
		Width: Variable	
		Length: Variable	
C		Height: 2 3/8	60
		Width: Variable	
		Length: Variable	
D		Height: 2 3/8	60
		Width: Variable	
		Length: Variable	
E		Height: 2 3/8	60
		Width: Variable	
		Length: Variable	
F		Height: 2 3/8	60
		Width: Variable	
		Length: Variable	
G		Height: 2 3/8	60
		Depth: Variable	
		Length: Variable	

